

General Equipment

GENERAL SPECIFICATIONS

• L.O.A	10.34 m
Length of hull	9.99 m
• L.W.L.	9.35 m
Width of hull	3.65 m
Lightweight	5 620 kg
Draft Standard Deep draught keel Cast iron	1.82 m
• Draft Optional extra Shallow draught keel Cast iron	1.37 m
Air draught	15.25 m
Freshwater capacity	290 I
Fuel tank capacity	130 I
Engine power	21 - 29 HP

ARCHITECTS / DESIGNERS _____

- Architect Naval: Finot Conq And associsArchitecture interior: Nauta Design

EC CERTIFICATE_____

Versions Deep draught keel (Standard)	Versions Shallow draught keel (optional extra)
6	-
7	7
8	8
10	10
	draught keel (Standard) 6 7 8

STANDARD SAIL LAYOUT AND AREA

30.00 m ²
105 % - 32.00 m ²
68.30 m ²
12.88 m
4.18 m
12.10 m
3.90 m







Version 2 Cabins



Version 3 Cabins



General Equipment

STANDARD EQUIPMENT

CONSTRUCTION

- Design made following European Directive requirements and according to EC certification
- · Monolithic hull design in polyester
- Monolithic structural counter moulding laminated and stuck to hull
- Deck in sandwich (glass fibre and balsa wood) Diamond tip type non-slip covering
- Deck hull join screwed, stuck and banded with 1 soild wood bulwark, screwed
- Cast iron keel fixed with bolts and stainless steel veneer and stuck
- · Hung rudder with stainless steel stock
- · White coloured hull Hull decorated in pearl grey

DECK EQUIPMENT

RIGGING

- Standard mast 9/10 electro-polished aluminium installed on the deck, 2 level(s) of advanced cross trees
- · Boom in anodised aluminium
- Standing rigging in single-strand stainless steel (Forestay -Side shrouds - Backstay)
- · 2 Backstays with turnbuckles
- 1 Standard fore stay
- 1 Rigid boom down-haul with tackle
- 1 Genoa furling system with drum on the deck
- · 2 Mainsail sheet bolts
- 2 genoa sheet tracks with piston adjusted traveller cars 2 Genoa sheet return blocks
- Rigging run back to cockpit (except boom topping lift Foot tuning line)
- Complete running rigging: 1 Main halyard 1 Genoa halyard with clutch on mast and cleat - 1 Boom topping lift with cleat on mast - 1 Mainsail foot - 1 Main sheet - 2 Genoa sheets - 2 fast reefing ropes
- 5 clutches to port
- 3 Bollards

WINCHES

- 2 Self-tailing genoa sheet winches (H40.2 STC)
- 1 Rigging winch self tailing on deck house port side (H35.2 STC)
- 1 Winch handle aluminium
- 1 Winch handle box

SAILS

- 1 Furling genoa with UV protective strip
- · 1 Classical mainsail, written, half-battened with slider
- · System Lazy Jack and Easy bag in Perle colour

MOORING -ANCHORING

- Self-bailing chain locker Clench bolt Hatch cover
- Single roller stainless steel bow fitting
- Mechanically welded stainless steel roller
- 6 Aluminium mooring cleats Stainless steel deck line protection

PERSONNEL GUARDS

- · Stainless steel pulpit 2 sections
- · 2 stainless steel aft pushpits
- 1 Ring lifebuoy bracket
- 1 Flag pole socket
- · Double stainless steel guardrails, Stainless steel stanchions

COCKPIT

Cockpit bottom self bailing in polyester

- 1 Wet locker to port (Life raft storage, Gas box 2 bottles)
- 1 Starboard locker (Sail locker)
- · 1 Locker next to tiller seat to starboard
- · Cockpit benches decked in natural solid wood
- 1 Steering wheel console: Leather covered steering wheel (900 mm diameter) - 1 Rudder system on column - 1 metal cable transmission system - 1 Stainless steel guard rail - navigation instrument stand (optional instruments) -
 - 1 Compass on binnacle
- · Engine control Control panel to starboard
- 1 Deck hole for access to tiller system 1 Emergency tiller
- Companionway hatch and door in PMMA

SUN DECK AND UPPER STERN

- Vertical opening access door assisted by gas piston Stainless steel
- 1 Stainless steel swimming ladder
- · 1 Cockpit shower spray cold water

FITTINGS

- · Alpi woodwork in fruit tree colour
- · Parquet type laminated floors
- · Hull spar ceilings in cabins and saloon

COMPANIONWAY

- Height to deck beam: 1.88 m
- · Companionway and steps in polyester
- 2 Stainless steel guardrails (Version 2 aft cabin(s)) 1 Stainless steel guardrails (Version 1 oft public)
 - 1 Stainless steel guardrails (Version 1 aft cabin)
- 1 Fixed zenital window with curtain

FORWARD CABIN

- Height to deck beam: 1.77 m
- Central double bed (2.05 m x 1.80 m x 0.35 m) 1 Marine mattress
- Double cupboard (Hanging locker Shelf) Cubby hole lockers
 Storage
- 1 Opening hatch(es) with curtain

SALOON

- Height to deck beam: 1.84 m
- U shaped saloon bench to port, double density foam
- · 1 Starboard bench seat
- · 4 Matching decorative cushions
- · Saloon table with wooden mounting
- Cubby hole lockers Bar storage space Storage space along the hull - Storage under bench seats
- 1 Port side window with curtain
- 2 opening porthole in side window To port
- 1 Starboard side window with curtain
- 2 opening porthole in side window To starboard (2 cabin version)
- 1 opening porthole in side window To starboard (3 cabin version)
- 2 Hull portholes with curtain
- 1 Opening deck hatch(es) with curtain



General Equipment

GALLEY TO PORT

- Height to deck beam: 1.85 m
- · L-shaped kitchen
- · White laminated worktop
- · 2 Rectangular stainless steel sinks
- 1 Mixer tap cold water / hot under pressure
- 1 2 hob gas cooker on mounting safety bar
- 1 Refrigerator 110 litre front opening Refrigeration unit 12 V
- 1 Dresser with drain system Closure / Cutting board
- · Cupboard Fitted storage space and lockers
- 1 Rubbish bin
- · 1 Porthole opening onto coamimg in side window

CHART TABLE TO STARBOARD

- · Facing companionway
- · Chart table with flaps and glove boxes- Moulded wood beading
- Pivoting electrical panel enabling access to electrical connections
- 1 White light fitting / Red
- · Storage cupboards and lockers with crockery rack
- 1 opening porthole(s) in side window

STARBOARD AFT WASHROOM

- Height to deck beam: 1.80 m
- Access through saloon
- · Washroom moulded in one piece to be watertight
- · Shower tray
- · Worktop with washbasin
- 1 Mixer tap / Shower hot / cold water
- 1 Manual marine toilet
- 1 Rigid sewage water tank 80L
- 1 Mirror
- Toilet accessories: Rubbish bin Paper dispenser peg towel rail
- Storage cupboard and lockers (1 In version 3 Cabins 2 In version 2 Cabins
- 1 Porthole(s) opening onto coaming with curtain
- 1 opening porthole(s) in side window (3 cabin version)
- 1 Opening porthole(s) with curtain on the cockpit end wall (2 cabin version)

AFT CABIN(S)

Version 1 forward cabin - 2 AFT cabin - 1 Toilet

- Height to deck beam: 1.90 m
- 2 Symmetrical aft cabin(s) with larger access to port cabin including:
- Height to deck beam: 1.94 m about
- Double bed (2.00 m x 1.45 m x 1.00 m) Marine mattress
- 1 Hanging locker
- 1 Porthole(s) opening onto coaming with curtain
- 1 Opening porthole(s) with curtain on the cockpit end wall

Version 1 forward cabin - 1 AFT cabin - 1 Toilet

- Height to deck beam: 1.90 m
- 1 Double bed(1.80 m to 2.10 M x 1.60 m) Marine mattress
- Bench seat Bed access sideboard
- Hanging locker Storage Glove box
- 1 Porthole(s) opening onto coaming with curtain
- 1 Opening porthole(s) with curtain on the cockpit end wall

ENGINE

- Engine Yanmar Diesel 21 hp
- Engine control fitted in cockpit
- Engine compartment: Soundproofing foam Ventilation: 1 air intake and 1 pressured air outlet
- 1 Alternator coupled to engine (60 Amperes)
- 1 Rotation moulded diesel tank 130 L (under starboard aft berth) - Electronic gauge - Low level alarm - 1 Deck filler
- Filters: Sea water Diesel Decanter
- · Stainless steel shaft line Polyester guard moulded into hull
- Fixed three blade propeller
- 1 Engine access through companionway (opening with 2 gas pistons)
- 2 Engine access through aft cabins (3 cabin version) or in the washroom and the aft cabin (2 cabin version)

ELECTRICITY

- 12 V circuit
- 1 service batteries 70 Amperes 1 Battery for engine 70 Amperes
- 1 Charge divider
- Electrical panel 12 V (Fuses Voltmeter 1 Water gauge -1 Fuel gauge - 1 Low battery charge warning - 1 Low diesel and water tank warning)
- 1 Cigar lighter socket 12 V
- Lighting: Fittings blanks Halogen ceiling lights 1 White/red light fitting
- Navigation lights: 1 Three-colour lights on masthead 1 Fire bicolor half-mast
- · Wire runs for options cables

PLUMBING

- 2 rotation moulded freshwater tanks (130 L port aft cabin -160 L forward cabin) - 2 Stainless steel water deck fillers -Separate tank filling - Tank selection with ¼ by-pass valves
- Pressurised electric water pump Expansion chamber -System protection filter
- 1 Electric water heater 25 L (engine run)
- 1 Rigid sewage water tank 80L
- Electric shower drain pump
- 1 Manual bilge pump 1 Electric bilge pump
- 1 Electric dresser drain pump

GAS

- 2 Gas bottle box(es) in the cockpit
- Pressure reducing valve and safety tap



General Equipment

TRIM LEVEL

	AVANTAGE	ELEGANCE
1 Notch color TFT ST70 RAYMARINE (Loch, Speedometer, Depth sounder)	•	•
Electric windlass 1000 W upward / Companionway - Remote control		•
High cupboards along hull in forward cabin	•	
De luxe saloon table	•	
Draining rack in dresser		•
Radio CD player / MP3 - 2 Interior loudspeakers - 2 Outside loudspeakers	•	•
Complete 220V electrical system (Inside sockets - Battery charger 25 Amperes - Shore power socket)		•
1 Additional service batteries 70 amperes		•
Hot/cold water cockpit shower hose		•
Companionway steps covered in wood		•
Leather covering on stainless steel saloon handrails - Stainless steel beading in saloon cubbyhole lockers		•
Freshwater foot pump - Sea water		•
Mirror on forward partition of fore cabin		•
1 Additional mirror in toilet closet (3 cabin version)		•
2 Additional mirror(s) in toilet closet (2 cabin version)		•
Delayed shower draining		
1 Additional opening cockpit porthole(s) to port in aft cabin(s)		•
1 Port opening aft platform porthole(s) in aft cabins		•
Mosquito blinds / Blackouts on deck hatches		•

OPTIONS

PACKS

PACK ELECTRONIC RAYMARINE

- Pickups Anemometer wind indicator ST70
- Multifunction screen C80 colour 8,4' (GPS tracker Cartography chart mapper Navionics Gold, supplied without chart)
- PC interface

PACK EASY DOCKING

- Side openings in guardrails
- Additional bow roller
- · White PCV steering wheel and console covers
- Mooring kit: (Anchor Britany 16 kg, 28 M of 10 mm chain, 40 M 18 mm rope) - 4 Mooring ropes - 6 Fenders

OTHER OPTIONS _

- Auto pilot SPX ST70 LS 40 Integrated gyrocompass Control panel on steering console
- VHF RAYMARINE 49E

- Engine Yanmar 29 HP
- Steel blue colour hull Hull decorated in pearl grey
- Electro-polished mast furling system with sail
- Wind indicator windex
- 2 flag halyards
- Asymmetric spinnaker rigging
- Easy Sail (Genoa traveller adjustment from cockpit Clutches on genoa sheet foot blocks - Backstay adjustment(s) - Winch handle Harken Speed Grip - 1 Winch handle box additional -Emergency rope cutter)
- · Mainsail sheet track on deck house
- 3 retractable blades propeller
- · Cockpit bottom and rear platform decked in natural solid wood
- · Catwalks decked in natural solid wood
- · Shore freshwater supply
- Outboard engine bracket
- Solid wood cockpit table Cover and lamp
- Perle deck house hood
- · Cockpit Bimini top Perle
- PVC cockpit cushions
- Berth in saloon
- Crockery kit marked Bénéteau
- Microwave oven (Version 2 cabin)
- Heating
- Porthole mosquito nets